

US and EU Export Controls

Technology Classification: ECCN: **EAR99** AL: **N** US-Content: **No**

This document is subject to national export control regulations. If US-Content is marked "Yes" then US reexport regulations apply. Diversion contrary to those regulations is prohibited. In case of doubt, Export Compliance Department must be contacted.

Dieses Dokument unterliegt nationalen Exportkontrollbestimmungen. Falls US-Content mit "Yes" gekennzeichnet ist, sind die US Reexport Bestimmungen anzuwenden.

Eine Weitergabe entgegen dieser Bestimmungen ist verboten. Im Zweifelsfall kontaktieren Sie Ihre ECC Abteilung.

SIEMENS

Ingenuity for life

Investigation of low cycle fatigue on large gas turbine casings

under consideration of geometric tolerances

Untersuchung der Lebensdauer von Gasturbinengehäusen unter

Berücksichtigung geometrischer Streuungen

Uwe Lohse Siemens AG Large Gas Turbines; Burkhard Voss Siemens AG Large Gas Turbines; Thorsten Lowitz Siemens AG Large Gas Turbines

Holger Schulze Spüntrup ITB Dortmund; Sebastian Wolff DYNARDO Austria

Restricted © Siemens AG 2017

siemens.com/powergeneration

Where we are – Gas Turbine Locations & Joint Venture Partners

SIEMENS

Technology Classification: ECC EAR99 AL:N US-Content: No



● Gas Turbines location
◆ JV location

The Siemens gas turbines portfolio: The right engine for every requirement

SIEMENS

Technology Classification: ECC EAR99 AL:N US-Content: No



Heavy-duty
gas turbines



Industrial
gas turbines



Aeroderivative
gas turbines



Power Generation / Mechanical Drive, Performance at ISO conditions

SGT5-8000H during assembly at Berlin plant

Efficiency:

- GT > 40 %
- GUD 61 %

With district heating
~85 %

Power:

- GT 425 MW
- CCPP 630 MW

Weight: ~445 t

Length: ~12,6 m

Diameter: ~5,5 m

Fleet: > 74 units



SGT5-8000H Plant Lausward Duesseldorf Press Release

SIEMENS

Düsseldorf. Siemens hat am 22. Januar 2016 das schlüsselfertig errichtete Gas- und Dampfturbinen (GuD)-Kraftwerk am Standort Lausward im Düsseldorfer Hafen an den Kunden und Betreiber Stadtwerke Düsseldorf AG übergeben. Das Kraftwerk wartet gleich mit drei neuen Rekorden im weltweiten Vergleich auf. In einer Testfahrt vor Abnahme wurde im Block „Fortuna“ eine maximale elektrische Leistung von 603,8 Megawatt (MW) erreicht, das ist eine neue Bestmarke für ein GuD-Kraftwerk dieser Auslegung. **Gleichzeitig wurde ein Wirkungsgrad von rund 61,5 Prozent nachgewiesen – ein neuer Weltrekord.**

Source:
WAZ
2016-01-28



Das neue Erdgaskraftwerk ist am Netz

Das Gas- und Dampfkraftwerk ist ein Meister der Wiederverwertung von Energie. Die Reibungsverluste, die bei der Umwandlung von Energie in Strom auftreten sind deshalb geringer als bei anderen Kraftwerken. Durch das Zusammenspiel mit **Fernwärme** erreicht das Kraftwerk einen **Wirkungsgrad von 85 Prozent** (bei Steinkohlekraftwerken liegt der Wert bei 45 Prozent). **Dank umweltschonender Technik werden im ersten Betriebsjahr 600.000 Tonnen CO2 eingespart, im Jahr 2025 sollen es über eine Million Tonnen sein.**


Source: RP 2016-01-29



Restricted © Siemens AG 2017

Key thermodynamic values for bolting design

Technology Classification: ECC-EAR99 AL:N US-Content: No



Motivation

Customer requirements

- Effective
- Reliable
- Available
- Flexible
- Cost effective

Und was heißt das im Kraftwerk vor Ort?

- Wegfall der Gewinnmarge -> Sparen, sparen, sparen ...
- bei beeinflussbaren Kosten wie Wartung, Reparatur
 - Instandhaltung bei Versagen und Verschleiß
 - Reparatur im Betrieb
 - Ausfall auch gewinnsteigernder Maßnahmen
- Outsourcing bis hin zu Personalabbau
- Flexible, vielseitig arbeitende Mitarbeiter
- ...

- Technische Herausforderungen
 - Neubewertung von Sicherheitsfaktoren und Lebenszeit
 - Hinterfragen von Betriebsanweisungen und -erfahrung
 - Ersatzbrennstoffe und Brennstoffband
 - Dehnung von Prüfintervallen
 - Neue technische Lösungen ...

Die Energiewende und die Rolle fossiler Kraftwerke

Dr. Lars Wiese, E.ON Kraftwerker

Leibniz Universität Hannover, Institut für Turbomaschinen und Fluid-Dynamik (TFD)
Ringvorlesung „Transformation des Energiesystems“ 23.04.2014



**Pushing design closer to the limits to fulfill
the customer requirements**

Motivation

With a classical deterministic approach it is difficult to fulfill the customer needs.

Safety factors for every impacted parameter used

- Material distribution
- Boundary condition
- Geometry variation


Probabilistic approach helps to fulfill the customer requirements

Only a probabilistic approach can consider the interaction of the impacted parameters

Effects on structural reliability / availability

Material


Material scatter of properties and fatigue curve
 Size effect also known as weakest link theory



$$F_{Ni}(n) = 1 - \exp\left(-\int_A \left(\frac{n}{N_{det}}\right)^m dA\right)$$


Geometry

Manufacturing tolerances




Loading

Transient
 Environment
 Operation



This project deals only with the geometry's effect

The idea



Quantify geometry scatter and assess the effects on the structural behavior and design life



How to:

- 3D-Scan existing geometries
- Compare scanned and nominal geometry
- Get the deviation of the actual geometry from the nominal geometry
- Apply the deviation on a FE-Model
- Compare scanned and nominal geometry and their utilization

Repeat for many different deviated geometries to obtain representative data


Challenges on scanning

- Huge amount of nodes from 180° scan
Nodes > 23.000.000
- Limited access for one scanner position due to the size of the object
- Limited time to scan in the production process
- Limited sample size due to long lead times
- Capability to repair and defeature scans required
(actual with *GEOMAGIC* or *GOM* possible)



**Improvement on scanning technic and
time wishful for daily user**

Impression of laser scan measurement



Photogrammetry system *GOM Tritop* in combination with the *GOM ATOS Triple Scan – Blue Light Scanner*.

Technology Classification: ECC EAR99 AL:N US-Content: No

Challenges on structure mechanic

3D FEA including bolting contact and thermal transient required for realistic stresses for LCF assessment

840.000 Nodes


380.000 Elements

>30 GB Disc space required

~ 3 Days on medium HPC hardware


⇒ Project time to run ~100 samples in robust analysis not feasible.

⇒ Disadvantage! Loss of global secondary membrane and bending effect on sub model.




**Actual solution: use a sub model of the
90° FEA model**

Challenges on structure mechanic



840.000 Nodes

- >30 GB Disc space required
- ~ 3 Days on medium HPC hardware
- ⇒ **Project time to run ~100 samples in robust analysis not feasible.**







240.000 Nodes

- ~7 GB Disc space per sample required
- ~ 90 min on medium HPC hardware
- ⇒ **~6 Days to run ~100 samples**

Trade-off between calculation time and result quality

Example of the sub Modell

Technology Classification: ECC EAR99 AL:N US-Content: No




Not machined surface.

Casting tolerance according ISO 8062

Statistics on Structures – How it works




Scan



Statistics on Structures (SoS)







Nominal geometry



Technology Classification: ECC EAR99 AL:N US-Content: No

Statistics on Structures – How it works





**1 Sample = 1 Scalar value
for the geometry deviation
per node and per scan**

Technology Classification: ECC EAR99 AL:N US-Content: No

Example of scanning results based on 8 samples



Mean deviation



Measured perpendicular to the surface coordinate; Normal vector direction

Example of scanning results based on 8 samples

Standard deviation




Basic statistic quantities can already be obtained

Example of scanning results based on 8 samples

Casting tolerances according ISO 8062-3


| | | | | | | | | | | | | | | | | | |
|-------|---------|--|--|--|--|--|--|--|--|-----|------|------|------|------|------|------|------|
| >4000 | ≤ 6300 | | | | | | | | | 7,0 | 10,0 | 14,0 | 20,0 | 28,0 | 35,0 | 44,0 | 56,0 |
| >6300 | ≤ 10000 | | | | | | | | | | 11,0 | 16,0 | 23,0 | 32,0 | 40,0 | 50,0 | 64,0 |

Absolute deviation: Mean+3·Sigma (~99.73%)



Tolerance class $n+1$

Tolerance class n



Basic quantities show critical locations for quality checks

Method to work with limited sample size

Empiric random field > 100 scans

Semi synthetic field ~5 scans used to calculate mean value and standard deviation. Field simulated at random with mean and STDDEV from small number of scans


Full synthetic Random simulations based on experiences from other projects or local CTQ records (critical to quality): CTQ are standard of the quality process but only local and can't include the full field information.

Decreased effort to collect data

Decreased effort to retrieve high quality results

Compromise between effort to collect data and the result quality needs to be discussed between the involved parties before the project starts.

Semi synthetic field




Linear combination of mean value and randomly scaled scatter shapes

perturbed geometry \approx μ mean value + ϕ_1 shape #1 $\cdot z_1$ + ϕ_2 shape #2 $\cdot z_2$ + ϕ_3 shape #3 $\cdot z_3$ + ϕ_4 shape #4 $\cdot z_4$ + ...


Semi synthetic field

Linear combination of mean value and randomly scaled scatter shapes




It's possible to create an arbitrary amount of different geometry variations

Workflow / Theory




Technology Classification: ECC EAR99 AL:N US-Content: No


Workflow / Theory



Mean temperature




Standard deviation of temperature



Technology Classification: ECC EAR99 AL:N US-Content: No


Workflow / Theory




Correlation of geometry scatter and temperature scatter

Technology Classification: ECC EAR99 AL:N US-Content: No
Scatter Shape 1
Scatter Shape 2
Scatter Shape 1

Workflow / Theory



Mean design life





Similarly, the workflow allows correlation of geometry scatter and design life scatter


Design Life

Mean design life

$$\frac{\text{Mean design life} - \text{Nominal design life}}{\text{Nominal design life}}$$





Design life difference due to probabilistic approach





Considering geometry scatter shows increased as well as decreased design life → Assessment of nominal geometry is globally a good approach

Design Life

Mean design life



Coefficient of Variation: $CoV = \frac{\sigma}{\mu}$




However, local scatter of design life can only be considered by probabilistic approach and may lead to different highly utilized locations

Technology Classification: ECC-FAP99-AL-NLUS-Content-No



Design Life

Mean design life



-3σ Design life

Minimal values for 99.7% of real geometries



However, local scatter of design life can only be considered by probabilistic approach and may lead to different highly utilized locations

Summary

- Synthetic random fields allow probabilistic assessment of structures with few available scans
- Software allows correlation of geometry scatter and result scatter
- Correlation of input and output allows identification of locations of uncritical geometry scatter with respect to design life. Tolerances can be adjusted accordingly.
- Easy statistical evaluation of the results plotted directly on the model in SoS
- Due to consideration of geometry scatter according safety factors may be adjusted
- Still some work to do...
 - Increase of sample size
 - Automatization of process
 - ...

Contact and Acknowledgement

Uwe Lohse Uwe.lohse@siemens.com

Burkhard Voss Burkhard.voss@siemens.com

Thorsten Lowitz Thorsten.lowitz@siemens.com

Sebastian Wolff sebastian.wolff@dynardo.at

Holger Schulze Spüntrup Holger.Schulze-Spuentrup@itb-fem.de

The presentation is based on the master thesis of Holger Schulze Spüntrup at Fachhochschule Dortmund, University of Applied Sciences

Referent Prof. Marius Geller, Fachhochschule Dortmund

Co-referent Sebastian Wolff, DYNARDO Austria GmbH

Technical support Dr. Frank Bremer



Ingenieurgesellschaft für technische Berechnungen mbH

Europaplatz 7, 44269 Dortmund

Tel.: +49 (0)231 94 53 65 - 21


Fax: +49 (0)231 94 53 65 - 11

Geschäftsführer: Dr. Frank Brehmer

Handelsregister Dortmund: HRB 16440

www.itb-fem.de

Pictures & logos taken from: www.dynardo.de and www.ansys.com



Thanks for your attention!

Disclaimer

This document contains forward-looking statements and information – that is, statements related to future, not past, events. These statements may be identified either orally or in writing by words as “expects”, “anticipates”, “intends”, “plans”, “believes”, “seeks”, “estimates”, “will” or words of similar meaning. Such statements are based on our current expectations and certain assumptions, and are, therefore, subject to certain risks and uncertainties. A variety of factors, many of which are beyond Siemens’ control, affect its operations, performance, business strategy and results and could cause the actual results, performance or achievements of Siemens worldwide to be materially different from any future results, performance or achievements that may be expressed or implied by such forward-looking statements. For us, particular uncertainties arise, among others, from changes in general economic and business conditions, changes in currency exchange rates and interest rates, introduction of competing products or technologies by other companies, lack of acceptance of new products or services by customers targeted by Siemens worldwide, changes in business strategy and various other factors. More detailed information about certain of these factors is contained in Siemens’ filings with the SEC, which are available on the Siemens website, www.siemens.com and on the SEC’s website, www.sec.gov. Should one or more of these risks or uncertainties materialize, or should underlying assumptions prove incorrect, actual results may vary materially from those described in the relevant forward-looking statement as anticipated, believed, estimated, expected, intended, planned or projected. Siemens does not intend or assume any obligation to update or revise these forward-looking statements in light of developments which differ from those anticipated.

Trademarks mentioned in this document are the property of Siemens AG, its affiliates or their respective owners.